

SECTION "C"  
(310 SQ. FT.)

SECTION "D"  
(940 SQ. FT.)

SECTION "A"  
(33,376 SQ. FT.)

SECTION "B"  
(20,432 SQ. FT.)

SECTION "E"  
(APPROX. 9,700 SQ. FT.)  
(ALL SHINGLE AREAS ON FRONT  
OF BUILDING)

- DRAIN W/EXIST TAPERED SUMP (TYP.)
- RAISED EQUIP. SUPPORT
- RAISED EQUIP. SUPPORT
- SCUPPER DRAIN (TYP.)
- RAISED EQUIP. SUPPORT
- CONDENSER ON 2'6" X 4' CURB - 1  
7' X 10' WRAPPED CURB - 1 (REMOVE CURB, CLOSE OPENING IN DECK, INFILL INSULATION TO MATCH HEIGHT OF EXISTING ROOF AND ROOF OVER AREA)
- PENETRATIONS LIST:  
CURBS:  
A - CHILLER UNITS ON 23' X 35' I-BEAMS WITH (4) 5" X 5" SQUARE SUPPORTS  
B - 7'6" X 44' RTU  
C - 4'6" X 7' RTU  
D - 3'6" X 5'6" RTU  
E - 3' X 4'6" RTU  
F - CHILLER UNIT ON 20' X 30' I-BEAMS WITH (16) 5" ROUND SUPPORTS  
G - 3'6" X 3'6" RTV  
H - 4' X 5' RTV  
ROOF HATCH - 3' X 3'6"  
PIPES  
1" - 11  
2" - 2  
3" - 2  
4" - 5  
5" - 4  
VENT STACKS  
8" - 4  
10" - 1  
RTV'S  
1'4" X 1'4" - 9  
1'9" X 1'9" - 1  
KITCHEN EXHAUST FANS  
2' X 2' - 3  
2'6" X 2'6" - 1  
SATELLITE DISH PADS (SET ON WALK PADS)  
3' X 3' - 1  
7' X 7' - 1  
UTILITY HOODS  
1'9" X 2' - 1  
2'6" X 2'6" - 1

EDGE CONDITIONS LEGEND:

- E1 - GRAVEL STOP EDGE METAL, REMOVE EXISTING EDGE METAL, INSTALL NEW GRAVEL STOP EDGE METAL W/ FULLY ADHERED FLASHING (SEE DET 0001)
- E2 - 0'-0" (H) TO 5'-2" (H)(VARIES) X 0'-4" (W) PARAPET WALL. REMOVE EXISTING EDGE METAL AND WALL FLASHINGS. INSTALL FULLY ADHERED WALL FLASHING UP OVER EXIST. TOP PLATE AND DOWN FRONT FACE, INSTALL NEW TWO PIECE METAL FASCIA (SEE DET. 0002)
- E3 - 3'-5" TO 4'-0" (H)(VARIES) EXISTING VERT. TRANSITION BETWEEN ROOF LEVELS. REMOVE ALL FLASHINGS. INSTALL FULLY ADHERED WALL FLASHING FULL HEIGHT AND TIE-IN TO FIELD MEMBRANE ON BOTH SIDES OF TRANSITION
- E4 - 3'-4" TO 5'-2" (H) WALL FLASHING, REMOVE FLASHINGS. INSTALL FULLY ADHERED NEW WALL FLASHING, INSTALL TERM BAR, SEALANT AND SLIP FLASHING TO BACKSIDE OF NEW SHINGLE EDGE METAL TO REMAIN (SEE DET 0003)
- E5 - 1'-0" (H) WALL FLASHING, REMOVE ALL FLASHINGS FULLY ADHERE NEW WALL FLASHING, INSTALL TERM BAR, SEALANT AND NEW SURFACE MOUNTED COUNTER FLASHING W/ SEALANT JOINT (SEE DET 0004)

NOTE: WHERE NEW SHINGLES ARE SPECIFIED TO BE INSTALLED ON OUTER FACE OF FASCIA METAL, INSTALL METAL SLIP FLASHING UNDER GRAVEL STOP AND OVER NEW SHINGLES

REMOVE AND RE-LINE ALL BUILT-IN GUTTERS AS PART OF SHINGLE REPLACEMENT (APPROX. 250 LIN. FEET)

General Notes



DISCLAIMER  
ALL DEAD, DESIGNED ARRANGEMENTS, AND PLANS INDICATED OR REPRESENTED BY THIS DRAWING ARE OWNED BY AND ARE THE PROPERTY OF ROOFINGPROJECTS.COM AND WERE CREATED, EVOLVED AND DEVELOPED FOR USE ON AND IN CONNECTION WITH THE SPECIFIED PROJECT. NONE OF SUCH LOGOS, DESIGNS, ARRANGEMENTS OR MARKS SHALL BE USED BY OR DISCLOSED TO ANY PARTISAN WHATSOEVER WITHOUT THE WRITTEN PERMISSION OF ROOFINGPROJECTS.COM.  
WRITTEN DIMENSIONS ON THIS DRAWING SHALL TAKE PRECEDENCE OVER SCALED DIMENSIONS. CONTRACTORS SHALL VERIFY AND BE RESPONSIBLE FOR ALL DIMENSIONS AND CONDITIONS ON THE JOB AND THIS OFFICE MUST BE NOTIFIED OF ANY VARIATIONS FROM THE DIMENSIONS AND CONDITIONS SHOWN BY THESE DRAWINGS.

No.	Revision/Issue	Date

Firm Name and Address  
RoofingProjects.com  
17 High Street  
Suite 301  
Norwalk, CT  
06851

Project Name and Address  
2026  
Shaws #553  
1 Chandler Dr  
Bath, ME 04530

Project	Sheet
Date May 4, 2026	1
Scale 3/32" = 1'-0"	